

數位話纜

- 適用領域及範圍：輕便耐用，具良好遮蔽效果。
- 導體：軟銅單線
- 絕緣：PE 氯乙烯
- 遮蔽：鋁箔麥拉帶
- 被覆：PE 聚氯乙烯



FS-JF-LAP 充膠話纜

- 適用領域及範圍：機械強度佳，具有良好遮蔽及保護效果。
- 導體：軟銅單線
- 絕緣：PE 氯乙烯
- 填充：防水充膠混合物
- 包帶：麥拉帶、不織布帶或紙帶
- 被覆：包帶外縱包鋁帶基層，外覆黑色 PE 聚乙烯形成 LAP 層

產品類別	產品編號	截面積 × 芯數 mm × C/P	導體	絕緣	被覆厚度 mm	完成外徑 mm
			構造 NO./mm	厚度 mm		
PE-PVC 充膠話纜	JF05010P	0.5 mm × 10 P	1/0.5	0.15	1.0	7.2
	JF05020P	0.5 mm × 20 P	1/0.5	0.15	1.0	9.1
	JF05030P	0.5 mm × 30 P	1/0.5	0.15	1.0	10.7
	JF05050P	0.5 mm × 50 P	1/0.5	0.15	1.2	13.5
	JF050100P	0.5 mm × 100 P	1/0.5	0.15	1.4	18.2
	JF050200P	0.5 mm × 200 P	1/0.5	0.15	1.6	24.8
	JF050300P	0.5 mm × 300 P	1/0.5	0.15	1.8	30.4
	JF050400P	0.5 mm × 400 P	1/0.5	0.15	2.0	34.5
	JF050600P	0.5 mm × 600 P	1/0.5	0.15	2.2	41.3
	JF050800P	0.5 mm × 800 P	1/0.5	0.15	2.3	46.5
	JF06510P	0.65 mm × 10 P	1/0.65	0.20	1.0	8.9
	JF06520P	0.65 mm × 20 P	1/0.65	0.20	1.0	11.4
	JF06530P	0.65 mm × 30 P	1/0.65	0.20	1.2	13.9
	JF06550P	0.65 mm × 50 P	1/0.65	0.20	1.4	17.4
	JF065100P	0.65 mm × 100 P	1/0.65	0.20	1.6	23.4
	JF065200P	0.65 mm × 200 P	1/0.65	0.20	1.8	32.0
JF065300P	0.65 mm × 300 P	1/0.65	0.20	2.2	39.6	
PE-PVC 充膠話纜	JF05010P	0.5 mm × 10 P	1/0.5	0.15	1.7	10
	JF05020P	0.5 mm × 20 P	1/0.5	0.15	1.7	12
	JF05030P	0.5 mm × 30 P	1/0.5	0.15	1.7	14
	JF05050P	0.5 mm × 50 P	1/0.5	0.15	1.7	16
	JF050100P	0.5 mm × 100 P	1/0.5	0.15	1.7	21
	JF050200P	0.5 mm × 200 P	1/0.5	0.15	1.8	27
	JF050300P	0.5 mm × 300 P	1/0.5	0.15	2.0	34
	JF050400P	0.5 mm × 400 P	1/0.5	0.15	2.1	39
	JF050600P	0.5 mm × 600 P	1/0.5	0.15	2.3	45
	JF06510P	0.65 mm × 10 P	1/0.65	0.20	1.7	12
	JF06520P	0.65 mm × 20 P	1/0.65	0.20	1.7	15
	JF06530P	0.65 mm × 30 P	1/0.65	0.20	1.7	17
	JF06550P	0.65 mm × 50 P	1/0.65	0.20	1.7	20
	JF065100P	0.65 mm × 100 P	1/0.65	0.20	1.8	27
	JF065200P	0.65 mm × 200 P	1/0.65	0.20	2.0	36
	JF065300P	0.65 mm × 300 P	1/0.65	0.20	2.2	42
JF065400P	0.65 mm × 400 P	1/0.65	0.20	2.3	48	
JF065600P	0.65 mm × 600 P	1/0.65	0.20	2.6	57	