

編織銅帶

- 適用領域及範圍：電機設備移動之電源引接、電腦儀器及各控制系統之接地線。
- 導體：鍍錫銅線 T.C
- 特性：柔軟度佳、繞曲性優。



產品類別	產品編號	截面積 mm ²	導體構造 NO./mm	寬度 mm	厚度 mm	耐電流 A
編織銅帶	CB00050	0.58 mm ²	0.12/48	1.5	0.4	10
	CB00075	0.75 mm ²	0.12/64	1.9	0.6	12
	CB00081	0.81 mm ²	0.12/72	2	0.5	15
	CB00108	1.08 mm ²	0.12/96	3.2	0.5	18
	CB00125	1.25 mm ²	0.12/112	3.2	0.58	20
	CB00140	1.4 mm ²	0.12/120	3.5	0.7	22
	CB00160	1.6 mm ²	0.12/144	3.8	0.82	23
	CB00200	2.0 mm ²	0.12/168	4.2	1.02	25
	CB00220	2.2 mm ²	0.12/192	4.5	1.1	28
	CB00270	2.7 mm ²	0.12/240	5.8	1.25	35
	CB00300	3.0 mm ²	0.16/144	6.2	1.2	40
	CB00350	3.5 mm ²	0.18/144	6.8	1.35	45
	CB00450	4.5 mm ²	0.12/384	11.8	0.95	55
	CB00550	5.5 mm ²	0.12/480	14.5	1.1	65
	CB00800	8.0 mm ²	0.12/704	8.8	1.7	80
	CB00800	8.0 mm ²	0.16/384	10.8	1.7	80
	CB01000	10 mm ²	0.16/480	16.8	1.32	90
	CB01400	14 mm ²	0.18/552	25	1.7	110
	CB01600	16 mm ²	0.18/624	27	1.6	120
	CB02200	22 mm ²	0.18/864	22.5	1.9	150
CB02500	25 mm ²	0.18/1008	25.4	2.2	160	
CB03800	38 mm ²	0.18/1488	30.8	2.6	200	
CB05000	50 mm ²	0.18/1968	38.5	3.1	250	